



The PA3 Arrow is a safety grade flexible photoluminescent polyester film coated with a permanent acrylic adhesive that has been designed to exceed requirements for emergency egress and other safety standards.

CONSTRUCTION

The PA3 Photoluminescent Arrow is designed with a flexible photoluminescent polyester film. It is coated with permanent acrylic adhesive powder.

ELECTRICAL COMPONENTS

The PA3 Photoluminescent Arrow does not require any type of electrical components.

INSTALLATION

The PA3 Photoluminescent Arrow is designed for indoor safety applications such as safety signage in building, marine, rail, marine, and military applications for IBC/IFC code compliant materials.

FEATURES

- Non-Toxic, thin gauge polyester film
- Peel-off adhesive backing makes installation easy and low-cost
- Requires 54 LUX (5-ft candles) of LED, fluorescent, metal halide or mercury vapor light to charge material for 60 minutes
- Install indoors only
- Long life expectancy
- High tack backing sticks to rough surfaces
- No future hazmat disposal needed

WARRANTY INFORMATION

Any component that fails due to manufacturer's defect is guaranteed for 1 year. The warranty only covers products installed and maintained in accordance with the instructions provided by their respective manufacturer and no warranty is made with respect to any of our products that are otherwise installed or maintained. For full warranty details, visit our Warranty Section.

Conformance to Codes and Standards

The PA3 Photoluminescent Arrow meets or exceeds the following codes: DIN 67510, ASTM 2072, ISO 15370, IMO RES A. 752 (18), EU marine Equipment Directive, PSPA Class B

DIMENSIONS

